

SERIE 112A-AT

80-AT

AVO - Wheel with high temperature silicone rubber tyre and steel castor for industry, diameter 160mm ean 21621

Material: High temperature silicone
Rubber tyre

Core:
Steel

Application field:
Industry

Description:

High temperature silicone rubber tyre wheel 80 Shore A with flanges in zinc-chromium plated pressed steel. Hub on shielded ball bearings.

Medium duty castors:

In zinc-chromium plated pressed steel, turning on double rim of balls, with plate. Assembled with self-locking nut.

Product line: High temperature

EAN13:8018793216210 **EAN5:**21621 **Article code:**0108000160TCR



Features

Minimum temperature: -20

Maximum temperature: 120

Dynamic load capacity: 150 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	160
Band width (mm)	40
Hub width (mm)	55
Hub version	Ball bearing
Wheel hole (mm)	17
Bearing seat (mm)	/
Dynamic load capacity (DaN)	150
Colour	Red
Material	High temperature silicone Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	55
Ground clearance (mm)	197
Castor hole (mm)	/
Static load capacity (DaN)	190
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized