

SERIE 112A-AT

## 80A-AT

**AVO - Wheel with high temperature silicone rubber tyre and steel castor for industry, diameter 180mm ean 21622**

**Material:** High temperature silicone  
Rubber tyre

**Core:**  
Steel

**Application field:**  
Industry

**Description:**

High temperature silicone rubber tyre wheel 80 Shore A with flanges in zinc-chromium plated pressed steel. Hub on shielded ball bearings.

**Medium duty castors:**

In zinc-chromium plated pressed steel, fixed. Assembled with self locking nut.

**Product line:** High temperature

**EAN13:**8018793216227

**EAN5:**21622

**Article code:**01080A0180TCR



## Features

**Minimum temperature:** -20

**Maximum temperature:** 120

**Dynamic load capacity:** 170 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 80

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

|                             |                                       |
|-----------------------------|---------------------------------------|
| Diameter (mm)               | 180                                   |
| Band width (mm)             | 50                                    |
| Hub width (mm)              | 55                                    |
| Hub version                 | Ball bearing                          |
| Wheel hole (mm)             | 17                                    |
| Bearing seat (mm)           | /                                     |
| Dynamic load capacity (DaN) | 170                                   |
| Colour                      | Red                                   |
| Material                    | High temperature silicone Rubber tyre |
| Box pieces                  | /                                     |
| Hardness scale              | Shore A                               |
| Hardness                    | 80                                    |

## Support data

|                            |            |
|----------------------------|------------|
| Plate size (mm)            | 140X110    |
| Plate hole spacing (mm)    | 105X080    |
| Plate hole size (mm)       | 11X16      |
| Offset (mm)                | /          |
| Ground clearance (mm)      | 225        |
| Castor hole (mm)           | /          |
| Static load capacity (DaN) | 220        |
| Structure                  | Fixed      |
| Version                    | /          |
| Brake                      | /          |
| Plain axle                 | /          |
| Stem type                  | /          |
| Finishing                  | Galvanized |