

SERIE 16A-T

## 36-T

**AVO - Wheel with high temperature silicone rubber tyre and steel castor for industry, diameter 200mm ean 27666**

**Material:** High temperature silicone Rubber tyre

**Core:** Aluminum

**Application field:** Industry

**Description:**

Wheel with high-temperature silicone rubber tread 80 Shore A and aluminium wheel centre. Hub on shielded ball bearings.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate. Assembled with self-locking nut.

**Product line:** High temperature

**EAN13:**8018793276665 **EAN5:**27666 **Article code:**1403600200TCA



## Features

**Minimum temperature:** -40

**Maximum temperature:** 280

**Dynamic load capacity:** 300 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 80

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

|                             |                                       |
|-----------------------------|---------------------------------------|
| Diameter (mm)               | 200                                   |
| Band width (mm)             | 50                                    |
| Hub width (mm)              | 60                                    |
| Hub version                 | Ball bearing                          |
| Wheel hole (mm)             | 20                                    |
| Bearing seat (mm)           | 47X14                                 |
| Dynamic load capacity (DaN) | 300                                   |
| Colour                      | Red                                   |
| Material                    | High temperature silicone Rubber tyre |
| Box pieces                  | /                                     |
| Hardness scale              | Shore A                               |
| Hardness                    | 80                                    |

## Support data

|                            |            |
|----------------------------|------------|
| Plate size (mm)            | 140X110    |
| Plate hole spacing (mm)    | 105X080    |
| Plate hole size (mm)       | 11X16      |
| Offset (mm)                | 55         |
| Ground clearance (mm)      | 235        |
| Castor hole (mm)           | /          |
| Static load capacity (DaN) | 380        |
| Structure                  | Swivel     |
| Version                    | Plate      |
| Brake                      | /          |
| Plain axle                 | /          |
| Stem type                  | /          |
| Finishing                  | Galvanized |