

SERIE 112A-AT

80A-AT

AVO - Wheel with high temperature silicone rubber tyre and steel castor for industry, diameter 200mm ean 27897

Material: High temperature silicone
Rubber tyre

Core:
Steel

Application field:
Industry

Description:

High temperature silicone rubber tyre wheel 80 Shore A with flanges in zinc-chromium plated pressed steel. Hub on shielded ball bearings.

Medium duty castors:

In zinc-chromium plated pressed steel, fixed. Assembled with self locking nut.

Product line: High temperature

EAN13:8018793278973

EAN5:27897

Article code:01080A0200TCR



Features

Minimum temperature: -20

Maximum temperature: 120

Dynamic load capacity: 205 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	55
Hub version	Ball bearing
Wheel hole (mm)	17
Bearing seat (mm)	/
Dynamic load capacity (DaN)	205
Colour	Red
Material	High temperature silicone Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	/
Ground clearance (mm)	235
Castor hole (mm)	/
Static load capacity (DaN)	260
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized