

SERIE 112A-AT

80-AT

AVO - Wheel with high temperature silicone rubber tyre and steel castor for industry, diameter 250mm ean 21618

Material: High temperature silicone
Rubber tyre

Core:
Steel

Application field:
Industry

Description:

High temperature silicone rubber tyre wheel 80 Shore A with flanges in zinc-chromium plated pressed steel. Hub on shielded ball bearings.

Medium duty castors:

In zinc-chromium plated pressed steel, turning on double rim of balls, with plate. Assembled with self-locking nut.

Product line: High temperature

EAN13: 8018793216180

EAN5: 21618

Article code: 0108000250TCR



Features

Minimum temperature: -20

Maximum temperature: 120

Dynamic load capacity: 300 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	250
Band width (mm)	60
Hub width (mm)	64
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	/
Dynamic load capacity (DaN)	300
Colour	Red
Material	High temperature silicone Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	200X160
Plate hole spacing (mm)	150X115
Plate hole size (mm)	14X26
Offset (mm)	85
Ground clearance (mm)	302
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized