

SERIE 112A-AT

80B-AT

AVO - Wheel with high temperature silicone rubber tyre and steel castor for industry, diameter 80mm ean 19044

Material: High temperature silicone
Rubber tyre

Core:
Steel

Application field:
Industry

Description:

High temperature silicone rubber tyre wheel 80 Shore A with flanges in zinc-chromium plated pressed steel. Hub on shielded ball bearings.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem. Assembled with self-locking nut.

Product line: High temperature

EAN13:8018793190442 **EAN5:**19044 **Article code:**01080B0080TC6



Features

Minimum temperature: -20

Maximum temperature: 120

Dynamic load capacity: 50 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	80
Band width (mm)	25
Hub width (mm)	34
Hub version	Ball bearing
Wheel hole (mm)	8
Bearing seat (mm)	/
Dynamic load capacity (DaN)	50
Colour	Red
Material	High temperature silicone Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	106
Castor hole (mm)	/
Static load capacity (DaN)	70
Structure	Swivel
Version	Axle
Brake	/
Plain axle	12X30
Stem type	Threaded axle
Finishing	Galvanized