

SERIE 112SE

112SE

AVO - Wheel with superelastic rubber tyre for industry, diameter 180mm

Material: Superelastic Rubber tyre

Core: Steel

Application field: Industry

Description:

Wheel with super elastic rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings. 112SE wheel can be assembled with all medium duty castors.

Product line: Rubber tyre

EAN13:/ EAN5:/ Article code:031120S1800RN



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 170 DaN

Rotation: Roller bearing

Hardness scale: Shore A

Hardness: 70

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	180
Band width (mm)	50
Hub width (mm)	55
Hub version	Roller bearing
Wheel hole (mm)	17
Bearing seat (mm)	/
Dynamic load capacity (DaN)	170
Colour	Black
Material	Superelastic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	70

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/