

SERIE 180X

## 250XBISF

AVO - Wheel made of non-marking rubber tyre with aisi 304 stainless steel castor for industry, diameter 80mm ean 27967

**Material:** / **Core:** Polypropylene **Scope:** Industry

**Description:**

Wheel with synthetic rubber tread and thermoplastic rim. Thread guards made of pressed stainless steel AISI 304 or thermoplastic material.

**Furniture Castors:**

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with bolt hole, front brake and locking device to stop both wheel and rotation.

**Product line:** Stainless steel

**EAN13:**8018793279673 **EAN5:**27967 **Article code:**22250FA080X0G



## Features

<b>Minimum temperature:</b> -20	<b>Maximum temperature:</b> 80	<b>Dynamic load capacity:</b> 55 DaN
<b>Rotation:</b> Plain bore	<b>Hardness scale:</b> Shore A	<b>Hardness:</b> 85

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware
- Wood

## Wheel data

<b>Diameter (mm)</b>	80
<b>Band width (mm)</b>	23
<b>Hub width (mm)</b>	29
<b>Hub version</b>	Plain bore
<b>Wheel hole (mm)</b>	8
<b>Bearing seat (mm)</b>	/
<b>Dynamic load capacity (DaN)</b>	55
<b>Colour</b>	Grey
<b>Material</b>	/
<b>Box pieces</b>	/
<b>Hardness scale</b>	Shore A
<b>Hardness</b>	85

## Support data

<b>Plate size (mm)</b>	/
<b>Plate hole spacing (mm)</b>	/
<b>Plate hole size (mm)</b>	/
<b>Offset (mm)</b>	30
<b>Ground clearance (mm)</b>	108
<b>Castor hole (mm)</b>	12
<b>Static load capacity (DaN)</b>	75
<b>Structure</b>	Swivel
<b>Version</b>	Bolt hole with brake
<b>Brake</b>	Front
<b>Plain axle</b>	/
<b>Stem type</b>	/
<b>Finishing</b>	AISI 304 stainless steel