

SERIE 112AM

## 80B-AM

**AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 80mm ean 28086**

**Material:** Non-marking Rubber tyre

**Core:** Steel

**Application field:** Industry

**Description:**

Wheel with no-marking rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

**Medium duty castors:**

In zinc-chromium plated pressed steel, turning on double rim of balls. Assembled with self locking nut. Dust cover ring on the balls.

**Product line:** Rubber tyre

**EAN13:**8018793280860

**EAN5:**28086

**Article code:**01080B00806BG



## Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 50 DaN

**Rotation:** Plain bore

**Hardness scale:** Shore A

**Hardness:** 80

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

|                             |                         |
|-----------------------------|-------------------------|
| Diameter (mm)               | 80                      |
| Band width (mm)             | 25                      |
| Hub width (mm)              | 40                      |
| Hub version                 | Plain bore              |
| Wheel hole (mm)             | 12                      |
| Bearing seat (mm)           | /                       |
| Dynamic load capacity (DaN) | 50                      |
| Colour                      | Grey                    |
| Material                    | Non-marking Rubber tyre |
| Box pieces                  | /                       |
| Hardness scale              | Shore A                 |
| Hardness                    | 80                      |

## Support data

|                            |               |
|----------------------------|---------------|
| Plate size (mm)            | /             |
| Plate hole spacing (mm)    | /             |
| Plate hole size (mm)       | /             |
| Offset (mm)                | 37            |
| Ground clearance (mm)      | 106           |
| Castor hole (mm)           | /             |
| Static load capacity (DaN) | 70            |
| Structure                  | Swivel        |
| Version                    | Axle          |
| Brake                      | /             |
| Plain axle                 | 12X30         |
| Stem type                  | Threaded axle |
| Finishing                  | Galvanized    |